

Options	110	260	410	750	1080	1400	2200	Order no.
Chamber modification for the application of reinforced perforated stainless steel shelves or stainless steel grids (bearing rails mounted in the working chamber) – includes replacement of 2 standard grids by 2 reinforced grids								K1
Light module cold white 6,500K LED light strips arranged on the side walls of the interior; 10 for model 110, 14 for model 260/400/750, programme controlled dimming from 0 to 100% (in 1 % steps), ramp programming in combination with temperature and humidity (not in combination with F6, F7)								T7
Light module cold white 6,500K + warm white 2,700K LED light strips - 10 stripes for model 110, 14 for model 260/400/750 (5 resp. 7 alternating coldwhite light strips and 5 resp. 7 warm white light strips) on the side walls of the interior, programme-controlled dimming from 0 to 100% (in 1 % steps), ramp programming in combination with temperature and humidity (not in combination with F6, F7)								T8
Light module warm white 2,700 K light strips arranged on the side walls of the interior, 10 strips for model 110, 14 for model 260/400/750, programme-controlled dimming from 0 to 100% (in 1 % steps), ramp programming in combination with temperature and humidity (not in combination with F6, F7)								T9
Interior socket, ampacity 230 V/2.2 A, can be switched off with the On/Off switch, cannot be switched individually, moisture tight IP68								R3
Entry port, 23 mm clear diameter, for introducing connections at the side, moisture tight, can be closed by flap and silicone stopper, standard position								
left centre/centre								F0
left centre top								F1
right centre/centre								F2
right centre top								F3
Entry port, 23 mm clear diameter for introducing connections at the side, moisture tight, can be closed by flap and silicone stopper (please, state location)								
left								F4
right								F5
rear								F6
Entry port (silicone), 40 mm clear diameter, moisture tight, can be closed by silicone stopper, at the back (please, state location; not in combination with T7, T8, T9)								F7
Entry port (silicone), 40 mm clear diameter, moisture tight, can be closed by silicone stopper, standard position rear (not in combination with T7, T8, T9)								D8
4 – 20 mA current loop interface (-10 to +80°C corresponds to 4 to 20 mA) Temperature controller, actual value								V3
Werkskalibrierzertifikat für je einen (frei wählbaren) Temperatur- und Feuchtwert Works calibration certificate for one (freely selectable) temperature and humidity value								DO0105
Compressed air dehumidification (efficient dehumidification of the interior by means of compressed air). Standard works calibration certificate (measuring point chamber centre) at +10 °C with 10 % rh.								C9
Door with lock (safety lock), Standard								B6
with SN/SF and SNplus/SFplus 450 and 750								B62
one lock								B63
two locks (one each door)								
three locks (one each door)								
Potential-free contact for combination error message (e.g. supply failure, sensor fault, fuse)								H6
Process-dependent programmable door lock (only for units with TwinDISPLAY)								D4
one interlocking system								D42
two interlocking systems (one each other)								D43
three interlocking systems (one each other)								
Door-open-recognition (only for units with TwinDISPLAY)								V5
one door-open-recognition								V52
two (one each door)								V53
three (one each door)								
MobileALERT, notification by SMS in case of any error or alarm of the device. Requires option H6 "floating contact for alarm"								C3
MobileALERT for 2 alarm notifications; notification by SMS; temperature and humidity alarm								C4
Castor frame (2-part), height 140 mm								R9
Temperature restriction; Temperature: +60 °C								A8

Accessory	110	260	410	750	1060	1400	2200	Order no.
Stainless steel grids, electropolished (standard equipment)	E20165	E2891		E20182	B41251	B38955		
Reinforced stainless steel grid, electropolished, max. loading 60 kg (model 750 with guide bars and fixing screws and only in connection with option K1)	E29767	E29766		B32190	B232550			
Perforated stainless steel shelves	B00325	B29725		B00328				
Reinforced perforated stainless steel shelf, max. loading 60 kg, with guide bars and fixing screws and only in connection with option K1)				B32191	B32549			
Stainless steel slide-in drip tray, 15 mm rim (may affect the temperature distribution) - cannot be used in connection with option K1	E02073	E29726		E02075	B32599			
Max. loading per slide-in drip tray (kg)	3	4		8				
Stainless steel slide-in drip tray, 15 mm rim, with guide bars and fixing screws (may affect the temperature distribution) - can be used only in connection with option K1				B32763				
Stainless steel bottom drip tray, 15 mm rim (may affect the temperature distribution) - cannot be used in connection with option K1	B04359	B29722		B04362	B29769			
Max. loading per bottom drip tray (kg)	3	4		8				
Stainless steel bottom drip tray, 15 mm rim (may affect the temperature distribution) - can be used only in connection with				B34055				
Holder for water tank (sizes 110 - 750: 2.5 litres, sizes 1060/1400/2200: 10 litres) for mounting on the rear of the appliance. Standard equipment for sizes 750, 1060, 1400 und 2200.	E32172							
Central water supply with filter cartridges for connection to the domestic water supply. Product information on demand.								ZWR6
Central water supply without filter cartridges for connection to the domestic water supply (only for demineralised water with a conductivity of 5 to 10 µS/cm and a pH value between 5 and 7). Product information on demand								ZWR7
USB-Ethernet adaptor								E06192
Ethernet connection cable 5 m for computer interface								E06189
USB User-ID stick (with User-ID licence): Oven-linked authorisation licence (User-ID-programme) on Memory-stick, prevents undesired manipulation by unauthorised third parties. When reordering please specify serial number (only for units with TwinDISPLAY)								B33170
USB stick with documentation software AtmoCONTROL and operation manual for products with SingleDISPLAY (the standard equipment of appliances with TwinDISPLAY includes one USB stick with AtmoCONTROL)								B33172
Set of height adjustable feet (4 pcs). Standard on models IC0med								B29768
Stacking set (4 pcs) for stacking of appliances of same size (not for models 160, 260, 450, 750, 1060, ICH110, ICH110L and ICH110C)								B29744
Flush-fit unit (stainless steel frame covering gap between oven and wall opening), with air slots - technical clarification required	B29734	B29738	B42116	B29742				
Flush-fit unit (stainless steel frame covering gap between oven and wall opening), without air slots - technical clarification required	B29735	B29739	B42117	B29743				
Subframe, adjustable in height (size 30 to 75: height 600 mm, size 110 to 450: height 500 mm)	B29749	B29751						
Subframe, on castors (size 30 to 75: height 660 mm, size 110 to 160: height 560 mm)	B29750							
Subframe, adjustable in height (height 130 mm, for example for units with fresh-air filter)	B33661	B33664						
FDA conforming software AtmoCONTROL (FDA edition). Meets the requirements for the use of electronically stored data sets and electronic signatures as laid down in Regulation 21 CFR Part 11 of the US Food and Drug Administration (FDA). Base licence for the control of one unit. Respective IQ/OQ documents available in German and English language (without surcharge)								FDAQ1
Integration of one additional unit (up to max. 15 units) into an already existent FDA-software licence								FDAQ2
IQ document with device-specific works test data, OQ/PQ check list as support for validation by customer								D00124
IQ/OQ document with works test data for chamber, incl. temperature distribution survey for one free-selectable temperature value, 9 measuring points (size 30), 27 measuring points (sizes 55 - 1060) to DIN 12880:2007-05 (further temperature values on demand), PQ check list as support for validation by customer								D00127
IQ/OQ document with device-specific works test data for one free-selectable temperature and humidity value, incl. temperature distribution survey at Memmert for 27 measuring points (26 measuring points on model HPP1400) to DIN 12880:2007-05, PQ check list as support for validation by customer (models HPP and ICH).								D00136
IQ/OQ document with device-specific works test data for one free-selectable temperature and humidity value, and measuring of light intensity, incl. temperature distribution survey at Memmert for 27 measuring points to DIN 12880:2007-05, PQ check list as support for validation by customer. Price for validation at customer site on demand (GER, AT, CH only)								D00137
External measuring instrument with sensors for daylight and UV-light. Product information on demand (models HPP, ICH L, IPPplus)								B04713
External measuring instrument with sensors with additional measuring head for temperature and humidity measurement. Product information on demand (models HPP, ICH, ICH L, ICH C, IPPplus and IC0med)								B04714