

| Options | 30 | 55 | 75 | 110 | 160 | 260 | 450 | 750 | 1060 | Order no. |
|---|----|----|----|-----|-----|-----|-----|-----|------|-----------|
| Extended overtemperature protection for SingleDISPLAY devices by additionally integrated Pt100 sensor for independent temperature monitoring for models UN/UF | | | | | | | | | | A6 |
| Temperature restriction - Temperatures: +60, +70, +80, +95, +100, +120, +160, +180, +200 or +250 °C (Please, indicate upon ordering) | | | | | | | | | | A8 |

| Accessory | 30 | 55 | 75 | 110 | 160 | 260 | 450 | 750 | 1060 | Order no. |
|---|--------|--------|--------|--------|--------|--------|--------|-----|--------|-----------|
| Stainless steel grids, electropolished (standard equipment) | E28884 | E20164 | | E20165 | | E28891 | E20182 | | B41251 | |
| Reinforced stainless steel grid, max. loading 60 kg, from size 450 with guide bars and fixing screws and only in connection | | | | E29767 | | E29766 | | | B32550 | |
| Perforated stainless steel shelf | B29727 | B03916 | | B00325 | | B29725 | B00328 | | | |
| Reinforced perforated stainless steel shelves, max. loading 60 kg, with guide bars and fixing screws and only in connection | | | | | | | | | B32549 | |
| Stainless steel slide-in drip tray, 15 mm rim (may affect the temperature distribution) - cannot be used in connection with option K1 | E02070 | E02072 | | E02073 | | E29726 | E02075 | | B32599 | |
| Max. loading per slide-in drip tray (kg) | | 1.5 | | 3 | | 4 | | 8 | | |
| Stainless steel bottom drip tray, 15 mm rim (may affect the temperature distribution) - cannot be used in connection with | B04356 | B04358 | | B04359 | | B29722 | B04362 | | B29769 | |
| Max. loading per bottom drip tray (kg) | | 1.5 | | 3 | | 4 | | 8 | | |
| Wall bracket for wall mounting | B29755 | B29756 | B29757 | B29758 | B29759 | | | | | |
| USB-Ethernet adapter | | | | | | | | | | E06192 |
| Ethernet connection cable 5 m for computer interface | | | | | | | | | | E06189 |
| USB User-ID stick (with User-ID licence): Oven-linked authorisation licence (User-ID-programme) on Memory-stick, prevents undesired manipulation by unauthorised third parties. When reordering please specify serial number (only for units with TwinDISPLAY) | | | | | | | | | | B33170 |
| USB stick with documentation software AtmoCONTROL and operation manual for products with SingleDISPLAY (the standard equipment of appliances with TwinDISPLAY includes one USB stick with AtmoCONTROL) | | | | | | | | | | B33172 |
| Set of height adjustable feet (4 pcs). Standard on models ICOMed | | | | | | | | | | B29768 |
| Stacking set (4 pcs) for stacking of appliances of same size (not for models 160, 260, 450, 750, 1060, ICH110, ICH110L and ICH110C) | | | | | | | | | | B29744 |
| Plug-in tube extension (outer diam. 60,3 mm, inner 57 mm), straight, for exhaust air ducting (if necessary for connection by hose), only models U, I, S | | | | | | | | | | B29718 |
| Plug-in tube extension (outer diam. 60,3 mm, inner 57 mm), angled, for exhaust air ducting (if necessary for connection by hose), only models U, I, S | | | | | | | | | | B29719 |
| Flush-fit unit (stainless steel frame covering gap between oven and wall opening), with air slots – technical clarification required | B29728 | B29730 | B29732 | B29734 | B29736 | B29738 | B29740 | | B29742 | |
| Flush-fit unit (stainless steel frame covering gap between oven and wall opening), without air slots – technical clarification required | B29729 | B29731 | B29733 | B29735 | B29737 | B29739 | B29741 | | B29743 | |
| Subframe, adjustable in height (size 30 to 75: height 600 mm, size 110 to 450: height 500 mm) | B29745 | B29747 | | B29749 | | B29751 | B29753 | | | |
| Subframe, on castors (size 30 to 75: height 660 mm, size 110 to 160: height 560 mm) | B29746 | B29748 | | B29750 | | | | | | |
| Subframe, adjustable in height (height 130 mm, for example for units with fresh-air filter) | B33657 | B33659 | | B33661 | | B33664 | | | | |
| Software conforming to FDA AtmoCONTROL. Meets the requirements for the use of electronically stored data sets and electronic signatures as laid down in Regulation 21 CFR Part 11 of the US Food and Drug Administration (FDA). Base licence for the control of one unit (only for units with TwinDISPLAY). Respective IQ/OQ documents available in German and English language (without surcharge) | | | | | | | | | | FDAQ1 |
| Integration of one additional unit (up to max. 15 units) into an already existent FDA-software licence | | | | | | | | | | FDAQ2 |
| IQ document with device-specific works test data, OQ/PQ check list as support for validation by customer | | | | | | | | | | D00124 |
| IQ/OQ document with works test data for chamber, incl. temperature distribution survey for one free-selectable temperature value. 9 measuring points (size 30), 27 measuring points (sizes 55 - 1060) to DIN 12880:2007-05 (further temperature values on demand), PQ check list as support for validation by customer | D00125 | | | | | D00127 | | | | |